

PRODUCT DATASHEET

HALO LP H₂O

TRACE MOISTURE IN HYDRIDE GASES



HALO LP H₂O offers:

- Low parts per billion (ppb) moisture detection capability in NH₃ and PH₃
- Absolute measurement (freedom from calibration gases)
- Wide dynamic range – over four orders of magnitude
- Low cost of ownership and operational simplicity
- Clean technology – no external calibration gases required
- Compact analyzer footprint
- User-programmable alarms immediately notify on high events

Specifications

Performance

Operating range:	See gas performance table below
Detection limit (LDL, 3σ/24h):	See gas performance table below
Precision (1σ, greater of):	$\pm 1\%$ or 1/3 of LDL
Accuracy (greater of):	$\pm 4\%$ or LDL
Speed of response:	< 3 minutes to 95%
Environmental conditions:	10°C to 40°C 30% to 80% RH (non-condensing)
Storage temperature:	-10°C to 50°C

Gas Handling System and Conditions*

Wetted materials:	316L stainless steel (corrosive gas version optional) 10 Ra surface finish
Gas connections:	1/4" male VCR inlet and outlet
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Inlet pressure:	10 – 125 psig (1.7 – 9.6 bara)
Outlet pressure:	<10 Torr (13 mbar)
Flow rate:	Up to 1.0 slpm
Sample gases:	NH ₃ , PH ₃ , AsH ₃ & inert matrices
Gas temperature:	Up to 60°C

Dimensions & Weight

Standard sensor (incl. shutoff valves):	H x W x D 8.73 x 8.57 x 26.4 in (222 x 218 x 670 mm)
Sensor rack (fits up to two sensors):	H x W x D 8.73 x 19.0 x 26.4 in (222 x 483 x 670 mm)
Standard sensor weight:	33 lbs (15.0 kg)

Electrical and Interfaces

Platform:	Max Series analyzer
Alarm indicators:	2 user programmable 1 system fault Form C relays
Power requirements:	90 – 240 VAC, 50/60 Hz
Power consumption:	40 Watts max. (excluding vacuum pump)
Signal output:	Isolated 4–20 mA
User interfaces:	5.7" LCD touchscreen. 10/100 Base-T Ethernet. USB, RS-232, RS-485. Modbus TCP (optional)
Data storage:	Internal or external flash drive
Certification:	CE Mark

*Vacuum source required

Standard Model

Performance, H₂O

	Range	LDL (3σ)	Precision (1σ) @ zero
In Ammonia:	0 – 20 ppm	9 ppb	3 ppb
In Phosphine [†] :	0 – 10 ppm	9 ppb	3 ppb
In Nitrogen:	0 – 6 ppm	1.0 ppb	0.3 ppb
In Argon:	0 – 4 ppm	0.8 ppb	0.25 ppb
In Hydrogen [†] :	0 – 6 ppm	1.0 ppb	0.3 ppb
In Helium:	0 – 3 ppm	0.6 ppb	0.2 ppb
In NO [†] :	0 – 100 ppm	16 ppb	6 ppb
In Germane [†] :	0 – 18 ppm	20 ppb	7 ppb

Arsine Model

Performance, H₂O

	Range	LDL (3σ)	Precision (1σ) @ zero
In Arsine [†] :	0 – 10 ppm	5 ppb	2 ppb
In Nitrogen:	0 – 6 ppm	1.0 ppb	0.3 ppb
In Argon:	0 – 4 ppm	1.0 ppb	0.3 ppb
In Hydrogen [†] :	0 – 6 ppm	1.0 ppb	0.3 ppb
In Helium:	0 – 3 ppm	1.0 ppb	0.3 ppb

[†]Low leak rate vacuum pump (safety certified for service in relevant gas) required.

Contact us for additional analytes and matrices.
U.S. Patent # 7,277,177

PREMIUM INSIGHTS – GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights' products and solutions deliver innovative and differentiated analysis and measurement solutions and technologies that add high value to our customers and protect the environment.

Our commitment is to deliver smart and affordable innovation that optimizes process, improves safety, and transforms our world.



OUR PREMIUM GLOBAL BRANDS

AQ ALPHA OMEGA
INSTRUMENTS

ATOM
INSTRUMENT

extrel

MBW calibration

COSAXENTAUR

HYGROCONTROL

LAR
THE
TOC
COMPANY

Tiger optics